

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Ljungdahl MS2002

Revision: 9/05/2019

Page 1 from 3

Reference nr DOP: 231537
Customer Ref nr DOP: LJ011031

Unique identification code of the product type:

Ljungdahl MS2002

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application, intended for use in cold climate.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Ljungdahl MS2002

Revision: 9/05/2019

Page 2 from 3

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Elastic recovery**	≥ 70%	
Secant modulus at 23°C (N/mm ²)	≤ 0.4	
Secant modulus at -20°C (N/mm ²)	≤ 0.6	
Secant modulus at -30°C (N/mm ²)	≤ 0.9	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	

Conditioning:

Method B

Test substrate:

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
B-2300 Turnhout, Belgium, 9/05/2019

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 9/05/2019

Page 3 from 3



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

19

Reference nr DOP: 231537

Customer Ref nr DOP: LJ011031

EN 15651-1: 2012

Sealant for facade for interior and exterior application, intended for use in cold climate.

Ljungdahl MS2002

EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM

Conditioning:

Method B

Substrate:

Mortar

Aluminium

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Elastic recovery**	≥ 70%	
Secant modulus at 23°C (N/mm ²)	≤ 0.4	
Secant modulus at -20°C (N/mm ²)	≤ 0.6	
Secant modulus at -30°C (N/mm ²)	≤ 0.9	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	