



# Declaration of Performance Sabaprotect M500

<b>Number: 100997/240914</b>	
<b>1. Unique identification code:</b>	Sabaprotect M500
<b>2. Batch number:</b>	Printed on packaging
<b>3. Intended use:</b>	a) Sealant for facade elements. b) Sealants for pedestrian walkways.
<b>4. Manufacturer:</b>	SABA Dinxperlo BV Industriestraat 3, 7091 DC Dinxperlo The Netherlands, +31 (0)315 65 89 99
<b>5. Authorized representative:</b>	N/A
<b>6. Systems of assessment of performance:</b>	System 3
<b>7. Harmonized standard:</b>	a) EN 15651-1, Type F 25LM INT-EXT b) EN 15651-4, Type PW 25LM INT-EXT
<b>8. Notified body: Issued: On the basis of:</b>	N/A

<b>9. Declared performance</b>			
Pre-conditioning: Method B			
Substrate: Concrete with SABA Primer 9002			
	<b>Essential characteristic</b>	<b>Performance</b>	<b>Technical specification</b>
<b>9.1</b>	Reaction to fire	Klasse E	EN 15651-1: 2012 & EN 15651-4:2012
<b>9.2</b>	Release of chemicals dangerous to the environment and health	See MSDS	EN 15651-1: 2012 & EN 15651-4:2012
Water tightness and air tightness			
<b>9.3</b>	Resistance to flow	≤ 2 mm	EN 15651-1: 2012
<b>9.4</b>	Loss of volume	≤ 10%	EN 15651-1: 2012 & EN 15651-4:2012

Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of SABA Dinxperlo BV, will apply to our recommendations, instructions for use and the delivery of our products.

Version number: 20-10-2014, superseding all previous versions

	Essential characteristic	Performance	Technical specification
Cohesion for cold climate areas			
9.5	Secant tensile modulus (100%) at - 30°C	NPD	EN 15651-1: 2012 & EN 15651-4:2012
9.6	Tensile properties at maintained extension at - 30°C	NPD	EN 15651-1: 2012 & EN 15651-4:2012
9.7	Tensile properties at maintained extension	Pass	EN 15651-4: 2012
9.8	Adhesion and cohesion properties at maintained extension after immersion in water	Pass	EN 15651-1: 2012
9.9	Adhesion and cohesion properties at maintained extension after 28 days of immersion in water	Pass	EN 15651-4: 2012
9.10	Adhesion and cohesion properties at maintained extension after 28 days of immersion in salt water	Pass	EN 15651-4: 2012
9.11	Tear resistance	Pass	EN 15651-4: 2012
9.12	Durability	Pass	EN 15651-1: 2012 & EN 15651-4:2012

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



SABA Dinxperlo BV  
Drs. R.F. de Block, Chief Technology Officer

Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of SABA Dinxperlo BV, will apply to our recommendations, instructions for use and the delivery of our products.

Version number: 20-10-2014, superseding all previous versions